



### Miniature tri-axial IEPE accelerometer

#### Dynamic

Sensitivity, $\pm 10\%$ , 25°C.....	2.5 mV/g
Acceleration range .....	2000 g peak
Amplitude nonlinearity.....	1%
Frequency response:	
$\pm 10\%$ .....	1 - 9000 Hz
$\pm 3$ dB.....	0.5 - 11000 Hz
Resonant frequency.....	42 kHz
Transverse sensitivity, max.....	5% of axial
Temperature response:	
$-55^{\circ}\text{C}$ .....	-10%
$+125^{\circ}\text{C}$ .....	+10%

#### Electrical

Power requirement: voltage source .....	18 - 30 VDC
current regulating diode .....	2 - 10 mA
Electrical noise, Broadband Spectral (g):	
2 Hz to 20 kHz.....	6 mg
Output impedance, max.....	100 $\Omega$
Bias output voltage.....	8 - 12 VDC
Grounding.....	Case grounded

#### Environmental

Temperature range.....	-55 to 125°C
Vibration limit.....	2000 g peak
Shock limit.....	5000 g peak
Electromagnetic sensitivity, equiv g, max .....	90 $\mu\text{g/gauss}$
Sealing .....	Hermetic
Base strain sensitivity, max.....	0.0002 g/ $\mu\text{strain}$




#### Physical

Sensing element design.....	Ceramic/shear
Weight.....	4.3 grams
Case material.....	Titanium
Output connector.....	4 pin

#### Accessories

- Mounting stud: M3
- Mating cable with BNCx3 output
- Calibration certificate

Note: Frequency response limits spectral and noise values are typical



#### Ordering Information

730A-2000

